

MiniP100

MINI DRY BATH FOR LABORATORY



Introduction

TOP INSTRUMENT Mini Dry Bath is a laboratory device used for heating samples in small tubes or vials. It is a compact and efficient instrument that can maintain precise temperature control of the samples.

Features

- Mini, lightweight, safe with LCD display.
- Digital control over both temperature and time.
- Built-in user recalibration function guarantees long term temperature accuracy.
- Overheating protection.
- Optional cooling function.
- Interchangeable blocks for a wide variety of test tube sizes.
- Mini, lightweight, safe with LCD display.
- Digital control over both temperature and time.
- Built-in user recalibration function guarantees long term temperature accuracy.
- Overheating protection.
- Optional cooling function.
- Interchangeable blocks for a wide variety of test tube sizes.

Technical parameter

Display	LCD
Temperature setting range [° C]	25~100
Temperature control range [° C]	room temperature +5~100
Temperature control accuracy [° C]	± 0.5
Temperature adjustment accuracy [° C]	0.1
Heating time (25 °C ~100 °C)	20min
Cooling time (20 °C ~0 °C)	/
Maximum heating rate	6.5 ° C /min
Maximum cooling rate	/
Timing range	0~999min/0~999sec
Program	9 programs (2 segments each)
Quick Calibration	Support
USB interface protocol	support
Error code prompt	support
Dimensions [length*width*height mm]	110*162*140
Machine weight [kg]	1
Power supply [v]	DC12V, 100~240V, 50/60Hz
Maximum power [w]	60
Working temperature [° C]	+10~40